

INTI INTERNATIONAL UNIVERSITY

Faculty of Engineering and Quantity Surveying

**EFFECT OF AGGREGATE TO CEMENT RATIO ON THE
PERFORMANCE OF PERVIOUS CONCRETE**

KIEW JIE FU

B.Eng (Hons) in Civil Engineering

Dr. Chang Fung Lung

Final Year Project

2018

SUPERVISOR'S DECLARATION

This project report entitled (Effect of Aggregate to Cement Ratio on the Performance of Pervious Concrete) is prepared and submitted by (KIEW JIE FU) as partial fulfilment of the requirement for Bachelor of Engineering (HONS) in Civil Engineering, INTI international University.

APPROVED BY:




Supervisor

CHAN FUNG WONG

Date : 04.05.2018

STUDENT'S DECLARATION

I hereby declare that the final year project is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at INTI INTERNATIONAL UNIVERSITY or other institutions.

Signature :  _____

Student Name : KIEW JIE FU

Student ID : I14004820

Date : 4 May 2018

ACKNOWLEDGMENT

Firstly, I would like to thank my supervisor, Dr. Chang Fung Lung for his extraordinary guidance and support in this thesis process as well as weekly meeting to ensure that I am in the right track in my research. Furthermore, I would like to express my gratitude to my friends, Yew Che chern, Lee Wei Sheng, and Jonathan Chee Wen Loon for helping me during concrete casting. Besides, I also want to thank my friend, Choong Mei Qi for helping me in ANOVA analysis for my collected data.

Furthermore, I would like to thank my family for giving me opportunity to pursue my degree in INTI INTERNATIONAL UNIVERSITY and financial support. Besides, I also want to appreciate lab assistant, Faiz for provide helps and tools whenever I need.

Lastly, I would like to thank my examiner, Mr Sudesh and Ir. Siow Yun Tong for giving their professional feedback in FYP 1. Besides, I also want to thank Mr Munir for giving a lot helpful advises and professional feedback in FYP 2.

ABSTRACT

Pervious concrete is a special concrete mixture designed to allow water infiltration. The effect of aggregate to cement ratio on the performance of pervious concrete is evaluated. The optimized aggregate to cement ratio used in pervious concrete had been indicated. Several test such as compressive strength test, density test, porosity test, and constant head water permeability test were conducted to determine the optimum aggregate to cement ratio incorporating 3:1, 4:1, 5:1, and 6:1. Specimen with higher aggregate to cement ratio achieve higher compressive strength and density but lower porosity and permeability. The result shown that specimen with 3:1 aggregate to cement ratio achieved highest average density of 1974 kg/m^3 and lowest porosity of 26.3 percent. Besides, specimen with 3:1 aggregate to cement ratio also achieve highest average compressive strength of 12.14 MPa and acceptable water permeability and porosity content at 28th day. On the other hand, the result indicate the specimen with 6:1 aggregate to cement ratio achieved lowest average compressive strength of 5.04 MPa and highest water permeability of 2.93 cm/s. Flaky shape of coarse aggregate which limited the compressive strength of pervious specimen achieved is not recommended to use.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	SUPERVISOR'S DECLARATION	ii
	STUDENT'S DECLARATION	iii
	ACKNOWLEDGMENT	iv
	ABSTRACT	v
	TABLE OF CONTENTS	vi
	LIST OF FIGURES	ix
	LIST OF TABLES	xii
	LIST OF ABBREVIATIONS	xiv
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problem Statement	2
	1.3 Objectives	3
	1.4 Scope of Study	3
	1.5 Significance of Study	3
2	LITERATURE REVIEW	4
	2.1 Pervious Concrete in General	4
	2.2 Properties of Pervious Concrete	5
	2.2.1 Compressive Strength	6
	2.2.2 Density and Porosity	9
	2.2.3 Permeability	10
	2.3 Factors Affecting Pervious Concrete	11
	2.4 Discussion	12
	2.5 Summary	15

3	METHODOLOGY	16
	3.0 Introduction	16
	3.1 Material	16
	3.1.1 Cement	18
	3.1.2 Aggregate	18
	3.1.3 Water	18
	3.2 Mix Proportion	18
	3.3 Experiment Setup	19
	3.3.1 Density Test	19
	3.3.2 Porosity Test	20
	3.3.3 Permeability Test	22
	3.3.4 Compressive Strength Test	24
	3.3.5 R-squared	25
	3.4 Summary	25
4	RESULTS AND DISCUSSION	26
	4.0 Introduction	26
	4.1 Sieve Analysis	28
	4.2 Compressive Strength Test	30
	4.3 Density Test	33
	4.4 Porosity Test	35
	4.5 Permeability Test	37
	4.6 Relationship of Density, Porosity and Permeability of Specimen	39
	4.7 Relationship of Compressive Strength, Porosity and Permeability of Specimen	41
	4.8 Porosity Versus Permeability	43
	4.9 ANOVA Analysis for Compressive Strength of Specimen	45
	4.10 ANOVA Analysis for Porosity of Specimen	49
	4.11 ANOVA Analysis for Density of Specimen	52
	4.12 ANOVA Analysis for Permeability of Specimen	55
	4.13 Failure Mode	56
	4.14 Summary	58

5	CONCLUSION AND RECOMMENDATIONS	59
	5.1 Conclusion	59
	5.2 Recommendations	60
REFERENCES		62-64
APPENDICES A-N		65-67

LIST OF FIGURES

	DESCRIPTION	PAGE
Figure 2.1	Open graded system of pervious concrete	5
Figure 2.2	Pervious concrete ball with difference water contents, i) water content too little , ii) water with proper amount, and iii) water contain too much (Tennis et al., 2004)	6
Figure 2.3	Noise absorbed by porous surface	7
Figure 2.4	Comparison between 18.75 mm and 9.375 mm sizes of compressive strength for 6:1 aggregate to cement ratio (Ajamu et al., 2012)	8
Figure 2.5	The difference between (a) constant head permeameter, and (b) falling head permeameter	10
Figure 2.6	Effect of A/C ratio on compressive strength of pervious concrete (Ghafoori and Dutta, 1995)	12
Figure 2.7	Relationship between water to cement ratio with compressive strength for pervious concrete 28-Days (Meininger and Richard, 1988)	13
Figure 2.8	Illustration of (a) lower aggregate to binder ratio and, (b) higher aggregate to binder ratio that results in the thickness of cement paste surrounding the aggregate particles	14
Figure 2.9	Relationship between volume of paste and compressive strength (Maguesvari and Narasimha, 2014)	14

Figure 2.10	Relationship between volume of paste content and permeability (Maguesvari and Narasimha, 2014)	15
Figure 3.1	Methodology chart of the project	17
Figure 3.2	Apparatus setup of porosity test	21
Figure 3.3	Setup of constant head water permeability test	23
Figure 3.4	Compressive strength test setup	24
Figure 4.1	Illustration of the specimens in different stage (a) Blended coarse aggregate from 14 mm stockpile, (b) Concrete casting by using concrete mixer, (c) Mold and samples, (d) Sample in curing tank at 100 percent relative humidity	27
Figure 4.2	The aggregate retained after the sieve analysis	28
Figure 4.3	Average of the aggregate passing through sieve size of 5mm, 10mm, and 14mm	29
Figure 4.4	Average of the aggregate retained between sieve size of 0mm to 5mm, 5mm to 10mm, and 10mm to 14mm	29
Figure 4.5	Average compressive strength with different aggregate to cement ratio toward different day	30
Figure 4.6	Specimen with 3:1 A/C ratio in age of 28 th after compressive strength test	33
Figure 4.7	Density of particular age with difference aggregate to cement ratio	34
Figure 4.8	The relationship between average density and average compressive strength of specimen in the age of 3, 7, 14, and 28	35
Figure 4.9	The relationship of porosity and the specimen with different A/C ratio	36
Figure 4.10 (a)	The relationship between the average permeability and the specimen with different A/C ratio	38

Figure 4.10 (b)	The relationship of average coefficient of permeability with the specimen with different A/C ratio	38
Figure 4.11	The relationship between average coefficient of permeability and aggregate to cement ratio in the age of 28 th days	38
Figure 4.12	The relationship between average porosity and density of specimen in age of 3 rd , 7 th , 14 th , and 28 th	40
Figure 4.13	The relationship between permeability and density of specimen in the age of 28 th days	40
Figure 4.14	Relationship between average coefficient of permeability and average density of specimen	41
Figure 4.15	The relationship between average compressive strength with average porosity of specimen in the age of 3 rd , 7 th , 14 th , and 28 th	42
Figure 4.16	Relationship between compressive strength and permeability of specimen in the age of 28 th days	43
Figure 4.17	Relationship between average compressive strength and average coefficient of permeability in the age of 28 th days	43
Figure 4.18	Relationship of permeability and porosity of specimen in age of 28 th days	44
Figure 4.19	Relationship of average porosity and permeability of specimen with difference A/C ratio	45
Figure 4.20	The specimen with 6:1 A/C ratio and specimen with 3:1 A/C ratio in the age of 28 th days	57
Figure 4.21	The failure mode of specimen with 6:1 A/C ratio after compressive strength test in the age of 28 th days	57
Figure 4.22	Crack traversing pattern in specimen of 3:1 A/C ratio and 6:1 A/C ratio	58

LIST OF TABLES

	DESCRIPTION	PAGE
Table 2.1	Pervious concrete typical mixtures (ACI 522R, 2010; NRMCA, 2004)	5
Table 2.2	7 th to 28 th days compressive strength range stated by various researchers	7
Table 2.3	Compressive strength with 0.40 water to cement ratio (Ajamu et al., 2012)	8
Table 2.4	Compressive strength and permeability with 0.35 w/c ratio and 9.5 mm aggregate size (Ibrahim et al., 2014)	9
Table 3.1	Mix proportion with w/c 0.31 and 350 kg/m ³ cement for different aggregate to cement ratio	18
Table 3.2	Number of pervious concrete specimens used	25
Table 4.1	Average compressive strength of four different aggregate to cement ratio incorporating 3:1, 4:1, 5:1, and 6:1	30
Table 4.2	Average porosity of four different aggregate to cement ratio incorporating 3:1, 4:1, 5:1, and 6:1	36
Table 4.3	ANOVA for compressive strength of specimens in the age of 3 rd days	46
Table 4.4	ANOVA for compressive strength of specimens in the age of 7 th days	47
Table 4.5	ANOVA for compressive strength of specimens in the age of 14 th days	47
Table 4.6	ANOVA for compressive strength of specimens in the age of 28 th days	48
Table 4.7	ANOVA for porosity of specimen in the age of 3 rd days	49
Table 4.8	ANOVA for porosity of specimen in the age of 7 th days	50

Table 4.9	ANOVA for porosity of specimen in the age of 14 th days	50
Table 4.10	ANOVA for porosity of specimen in the age of 28 th days	51
Table 4.11	ANOVA for density of specimen in the age of 3 rd days	52
Table 4.12	ANOVA for density of specimen in the age of 7 th days	53
Table 4.13	ANOVA for density of specimen in the age of 14 th days	53
Table 4.14	ANOVA for density of specimen in the age of 28 th days	54
Table 4.15	ANOVA for water permeability in the age of 28 th days	55

LIST OF ABBREVIATIONS

ACI	American Concrete Institute
A/C	Aggregate to cement ratio
ASTM	American Society for Testing and Materials
BSI	British Standard Institution
NRMCA	National Ready Mixed Concrete Association

CHAPTER 1

INTRODUCTION

1.1 Background

Permeable concrete or better known as porous concrete or pervious concrete is a unique concrete with open graded system which allow water to pass through by its porous properties. Pervious concrete generally consist of cement binder, water, coarse aggregate, admixture and little or no sand. The slump value from the slump test is around 0 mm to 25 mm in order to produce a dry mixes that can be used in paving machines with high-powered vibration (Ćosić *et al.*, 2015). Due to the high porosity, the strength and durability are relatively decreasing compared to conventional concrete. Thus, pervious concrete is normally used in low traffic volume road, parking areas, residential streets and sidewalk or pedestrian walkway (Ćosić *et al.*, 2015). Pervious concrete is very useful for flood control, handling water runoff, and increase skid resistant because of its high porosity. Centre for Watershed Protection, a non-profit organisation stated that installing pervious concrete is very economical due to the lower installation cost compare to traditional gutters, curbs, piping, retention basins, and storm drain inlets which cost approximately three times more than pervious concrete. Besides, pervious concrete can also improve the land utilizations by neglecting the require of detention basin (Ibrahim *et al.*, 2014a). On the other hand, pervious concrete save extra land for installation of additional filter system and large ponds in order to retain storm water. In additional to all the economical factor, pervious concrete also reduce the heat island issue by its light colour and open cell structure (Ajamu *et al.*, 2012). In general, pervious concrete have to satisfy the properties such as void content between 18 to 35% , size of connected pores range between 2 to 8 mm and range of 2.8 to 28 MPa compressive strength (Tho-In *et al.*, 2012).